

Cisco 500 Series Stackable Managed Switches

Advanced Features for Demanding Environments, at an Affordable Price

Your business is growing, and that means more customers, more opportunities, and more attention on your company. The only problem: Your network was built for a smaller operation. As you add more devices, applications, and users, your IT environment will become increasingly difficult and expensive to manage. Even worse, as the network becomes more complex and overloaded, your users are likely to see sluggish performance and even outages.

With more customers and employees depending on your business than ever before, a slow or unreliable network is simply not an option. You need an IT backbone that provides excellent performance, nonstop availability, and advanced security. The ideal network will be easy to manage, even as it supports more advanced features, and will be designed to grow with your company. And it is available at a price you can afford.

Cisco 500 Series Stackable Managed Switches

The Cisco® 500 Series Stackable Managed Switches (Figure 1) are a new line of stackable managed Ethernet switches that provide the advanced capabilities you need to support a more demanding network environment, at an affordable price. These switches provide 24 or 48 ports of Fast Ethernet and 24 to 52 ports of Gigabit Ethernet connectivity with optional 10 Gigabit uplinks, providing a solid foundation for your current business applications, as well as those you are planning for the future. At the same time, these switches are easy to deploy and manage, without a large IT staff.

Figure 1. Cisco 500 Series Stackable Managed Switches



Cisco 500 Series switches are designed to protect your technology investment as your business grows. Unlike switches that claim to be stackable but have elements which are administered and troubleshot separately, the Cisco 500 Series provides true stacking capability, allowing you to configure, manage, and troubleshot multiple physical switches as a single device and more easily expand your network. The Cisco 500 Series switch offer models which are fanless making it one of the industry's first in stackable switches, thereby delivering increased reliability, power efficiency, and minimizing noise.

A true stack delivers a unified data and control plane, in addition to management plane, providing flexibility, scalability, and ease of use since the stack of units operate as a single entity constituting all the ports of the stack members. The switches also protect your technology investment with an enhanced warranty, dedicated technical support, and the ability to upgrade equipment in the future and receive credit for your Cisco 500 Series switch. Overall, the Cisco 500 Series provides the ideal technology foundation for a growing business.

Features and Benefits

Cisco 500 Series switches provide the advanced feature set that growing businesses require, and that high-bandwidth applications and technologies demand. These switches can improve the availability of your critical applications, protect your business information, and optimize your network bandwidth to more effectively deliver information and support applications. The switches provide the following benefits.

Easy Deployment and Use

Cisco 500 Series switches are designed to be easy to use and manage by small businesses or the partners that serve them. They feature:

- Simple-to-use graphical interfaces reduce the time required to deploy, troubleshoot, and manage the network and allow you to support sophisticated capabilities without increasing IT head count.
- The switches also support Textview, a full command-line interface (CLI) option for partners that prefer it.
- Using Auto Smartports intelligence, the switch can detect a network device connected to any port and automatically configure the optimal security, quality of service (QoS), and availability on that port.
- Cisco Discovery Protocol (CDP) discovers Cisco devices and allows devices to share critical configuration information, simplifying network setup and integration.
- Support for Simple Network Management Protocol (SNMP) allows you to set up and manage your switches and other Cisco devices remotely from a network management station, improving IT workflow and mass configurations.
- The Cisco FindIT utility, which works through a simple toolbar on the user's web browser, discovers Cisco devices in the network and displays basic information, such as serial numbers and IP addresses, to aid in configuration and deployment. (For more information, and to download this free utility, please visit.

High Reliability and Resiliency

In a growing business where 24x7 availability is critical, you need to assure that employees can always access the data and resources they need. In these environments, stackable switches can play an important role in eliminating downtime and improving network resiliency. For example, if a switch within a Cisco 500 Series stack fails, another switch immediately takes over, keeping your network up and running. You can also replace individual devices in the stack without taking your network offline or affecting employee productivity.

The Cisco 500X models provide an additional layer of resiliency with support for the Virtual Router Redundancy Protocol (VRRP). VRRP lets you extend the same resiliency that stacking provides for individual switches to complete network domains. By running VRRP between two stacks, you can instantly cut over from one stack to another in the event of a problem, and continue operating even after a failure.

The Cisco 500 Series also supports dual images, allowing you to perform software upgrades without having to take the network offline or worry about the network going down during the upgrade.

Simplified IT Operation

Cisco 500 Series switches help optimize your IT operations with built-in features that simplify and streamline day-to-day network operation:

- True stacking allows you to troubleshoot, configure, and manage multiple physical switches as a single entity.
- Unlike other stacking switches that require uniform configurations, the Cisco 500 Series allows you to mix Fast Ethernet, Gigabit Ethernet, and 10 Gigabit Ethernet models in a single stack, providing total flexibility without sacrificing manageability.
- Cisco switches use common chipsets/software across all switching portfolios, so all Cisco switches within a category support the same feature set - making it easier to manage and support all switches across the network.

True Stacking

Some switches claim to support stacking but in practice support only “clustering” - meaning that each switch must still be managed and configured individually. Cisco 500 Series switches provide true stacking capability, allowing you to configure, manage, and troubleshoot all switches in a stack as a single unit, with a single IP address.

A true stack delivers a unified data and control plane, in addition to management plane, providing flexibility, scalability, and ease of use since the stack of units operate as a single entity constituting all the ports of the stack members. This capability can radically reduce complexity in a growing network environment while improving the resiliency and availability of network applications. True stacking also provides other cost savings and administrative benefits through features such as cross-stack QoS, VLANs, and port mirroring, which clustered switches can't support.

Strong Security

Cisco 500 Series switches provide the advanced security features you need to protect your business data and keep unauthorized users off the network:

- Embedded Secure Sockets Layer (SSL) encryption protects management data traveling to and from the switch.
- Extensive access control lists (ACLs) restrict sensitive portions of the network to keep out unauthorized users and guard against network attacks.
- Guest VLANs let you provide Internet connectivity to nonemployee users while isolating critical business services from guest traffic.
- Support for advanced network security applications such as IEEE 802.1X port security tightly limits access to specific segments of your network. Web based authentication provides a consistent interface to authenticate all types of host devices and operating systems, without the complexity of deploying IEEE 802.1X clients on each endpoint.
- Advanced defense mechanisms, including dynamic Address Resolution Protocol (ARP) inspection, IP Source Guard, and Dynamic Host Configuration Protocol (DHCP) snooping, detect and block deliberate network attacks. Combinations of these protocols are also referred to as IPMB (IP-MAC- port binding).

- IPv6 First Hop Security extends the advanced threat protection to IPv6. This comprehensive security suite includes ND inspection, RA guard, DHCPv6 guard and neighbor binding integrity check, providing unparalleled protection against a vast range of address spoofing and man in the middle attack on IPv6 networks.
- Time based ACLs and Port Operation restrict access to the network during predesignated times, such as business hours.
- Uniform MAC address-based security can be applied automatically to mobile users as they roam between wireless access points.
- Secure Core Technology (SCT) helps ensure that the switch is able to process management traffic in the face of a denial of service attack.
- Private VLAN Edge (PVE) provides Layer 2 isolation between devices on the same VLAN.
- Storm control can be applied to broadcast, multicast, and unknown unicast traffic.
- Protection of management sessions using Radius, TACACS+ and local database authentication as well as secure management sessions over SSL, SSH, and SNMPv3.
- DoS (denial-of-service) attack prevention maximizes network uptime in the presence of an attack.

Networkwide Automatic Voice Deployment

Using a combination of CDP, LLDP-MED, Auto Smartports, and VSDP (Voice Services Discovery Protocol - a unique Cisco protocol), customers can deploy an end-to-end voice network dynamically. The switches in the network automatically converge around a single voice VLAN and QoS parameters and then propagate them out to the phones on the ports where they are discovered. For example, automated voice VLAN capabilities let you plug any IP phone (including third-party phones) into your IP telephony network and receive an immediate dial tone. The switch automatically configures the device with the right VLAN and QoS parameters to prioritize voice traffic.

High-Power Power over Ethernet Plus (PoE+)

Cisco 500 Series switches support the Power over Ethernet Plus (PoE+) standard (IEEE 802. at), providing up to 30 watts per port. The power is managed in a smart fashion such that only the amount of power the endpoint needs is delivered to it and not wasted. As a result, the switches can support devices that require more power, such as dual-band 802.11n wireless access points, video-based IP phones, surveillance cameras, and more.

PoE capabilities simplify the deployment of advanced technologies by allowing you to connect and power network endpoints over a single Ethernet cable, without having to install separate power supplies. Cisco 500 Series switches are also fully backwards compatible with IEEE 802.11af PoE and previous- generation Cisco legacy PoE protocols.

IPv6 Support

As the IP address scheme evolves to accommodate a growing number of network devices, the Cisco 500 Series can support the transition to the next generation of networking and operating systems such as Windows 7, Vista, and Linux. These switches continue to support previous-generation IPv4, allowing you to evolve to the new IPv6 standard at your own pace, and helping ensure that your current network will continue to support your business applications in the future. Cisco 500 Series switches have successfully completed rigorous IPv6 testing and have received the USGv6 and IPv6 Gold certification.

Advanced Layer 3 Traffic Management

The Cisco 500 Series enables a more advanced set of traffic management capabilities to help growing businesses organize their networks more effectively and efficiently. For example, the switches provide static LAN Layer 3 routing, allowing you to segment your network into workgroups and communicate across VLANs without degrading application performance.

With these capabilities, you can boost the efficiency of your network by offloading internal traffic-handling tasks from your router and allowing it to manage primarily external traffic and security.

Cisco 500X models go even farther, providing dynamic Layer 3 routing features. With these capabilities, you can minimize the need to manually configure routing devices and simplify the ongoing operation of the network.

Power Efficiency

The Cisco 500 Series integrates a variety of power-saving features across all models, providing the industry's most extensive energy-efficient switching portfolio. These switches are designed to conserve energy by optimizing power use, which helps protect the environment and reduce your energy costs. They provide an eco-friendly network solution without compromising performance. Cisco 500 Series switches feature:

- Support for the Energy Efficient Ethernet (IEEE 802.3az) standard, which reduces energy consumption by monitoring the amount of traffic on an active link and putting the link into a sleep state during quiet periods
- The latest application-specific integrated circuits (ASICs), which use low-power 65-nanometer technology and low power high performance ARM CPUs
- Automatic power shutoff on ports when a link is down
- LEDs can be turned off to save power
- Embedded intelligence to adjust signal strength based on the length of the connecting cable

Expandability

The Cisco 500 Series provides more ports per Gigabit Ethernet switch than traditional switch models, giving you more flexibility to connect and empower your business. Gigabit Ethernet models feature 28- and 52-port switches, versus traditional devices that offer 20 or 44 ports, with 4 shared ports giving you more value. The Cisco 500 models offer 1G and 1G/5G Ethernet expansion slots, and the Cisco 500X models offer 10 Gigabit Ethernet expansion slots. As your business adds new applications, devices, and more bandwidth, you retain the flexibility to expand and interconnect your network infrastructure intelligently and efficiently, and reduce bottlenecks.

Peace of Mind and Investment Protection

Cisco 500 Series switches offer the reliable performance and peace of mind you expect from a Cisco switch. When you invest in the Cisco 500 Series, you gain the benefit of:

- Limited lifetime warranty with next-business-day (NBD) advance replacement (where available, otherwise same day ship)
- A solution that has been rigorously tested to help ensure optimal network uptime to keep employees connected to key resources and productive
- A solution designed and tested to easily and fully integrate with other Cisco voice, unified communications, security, and networking products, as part of a comprehensive technology platform for your business

Cisco Limited Lifetime Hardware Warranty

Cisco 500 Series switches offer a limited lifetime hardware warranty with NBD advance replacement (where available; otherwise same day ship) and a limited lifetime warranty for fans and power supplies.

World-Class Service and Support

Your time is valuable, especially when you have a problem affecting your business. Cisco 500 Series switches are backed by the Cisco Small Business Support Service, which provides affordable peace-of-mind coverage. This subscription-based service helps you protect your investment and derive maximum value from Cisco Small Business products. Delivered by Cisco and backed by your trusted partner, this comprehensive service includes software updates and access to the Cisco Small Business Support Center, and it extends technical service to three years.

Cisco Small Business products are supported by professionals in the Cisco Small Business Support Center, a dedicated resource for small business customers and networks, with locations worldwide that are specifically trained to understand your needs. You also have access to extensive technical and product information through the Cisco Small Business Support Community, an online forum that enables you to collaborate with your peers and reach Cisco technical experts for support information.

Product Specifications

Table 1. Product Specifications

Feature	Description		
Performance			
Switching capacity and forwarding rate All switches are wire-speed and non-blocking.	Product Name	Capacity in mpps (64-byte packets)	Switching Capacity (Gbps)
	SF500-24	9.52	28.8
	SF500-24P	9.52	28.8
	SF500-24MP	9.52	28.8
	SF500-48	13.10	33.6
	SF500-48P	13.10	33.6
	SF500-48MP	13.10	33.6
	SG500-28	41.67	72
	SG500-28P	41.67	72
	SG500-28MPP	41.67	72
	SG500-52	77.38	120
	SG500-52P	77.38	120
	SG500-52MP	77.38	120
	SG500X-24	95.24	128
	SG500X-24P	95.24	128
SG500X-24MPP	95.24	128	

Feature	Description		
	SG500X-48	130.95	176
	SG500X-48P	130.95	176
	SG500X-48MP	130.95	176
	SG500XG-8F8T	238.1	320
Layer 2 Switching			
Spanning Tree Protocol	Standard 802.1d Spanning Tree Support Fast convergence using 802.1w (Rapid Spanning Tree [RSTP]), enabled by default Multiple spanning tree instances using 802.1s (MSTP). 16 instances are supported		
Port grouping/link aggregation	Support for IEEE 802.3ad Link Aggregation Control Protocol (LACP) <ul style="list-style-type: none"> Up to 32 groups Up to 8 ports per group with 16 candidate ports for each (dynamic) 802.3ad LAG 		
VLAN	Support for up to 4096 VLANs simultaneously Port-based and 802.1Q tag-based VLANs MAC-based VLAN Management VLAN PVE (Private VLAN Edge), also known as Protected Port, with multiple uplinks Guest VLAN Unauthenticated VLAN Protocol-based VLAN CPE VLAN Dynamic VLAN assignment via Radius server along with 802.1x client authentication		
Voice VLAN	Voice traffic is automatically assigned to a voice-specific VLAN and treated with appropriate levels of QoS. Auto voice capabilities deliver network-wide zero touch deployment of voice endpoints and call control devices.		
Multicast TV VLAN	Multicast TV VLAN allows the single multicast VLAN to be shared in the network while subscribers remain in separate VLANs. This feature is also known as Multicast VLAN Registration (MVR).		
Q-in-Q	VLANs transparently cross over a service provider network while isolating traffic among customers.		
GVRP/GARP	Generic VLAN Registration Protocol (GVRP) and Generic Attribute Registration Protocol (GARP) enable automatic propagation and configuration of VLANs in a bridged domain.		
Unidirectional Link Detection (UDLD)	UDLD monitors physical connection to detect unidirectional links caused by incorrect wiring or port faults to prevent forwarding loops and blackholing of traffic in switched networks		
DHCP Relay at Layer 2	Relay of DHCP traffic to DHCP server in a different VLAN. Works with DHCP Option 82.		
IGMP (versions 1, 2, and 3) snooping	Internet Group Management Protocol (IGMP) limits bandwidth-intensive multicast traffic to only the requesters; supports 1K (1024) and 4K (for SG500X in native mode) multicast groups (source-specific multicasting is also supported).		
IGMP querier	IGMP querier is used to support a Layer 2 multicast domain of snooping switches in the absence of a multicast router.		
HOL blocking	Head-of-line (HOL) blocking.		
Jumbo Frames	Frames up to 9K (9216) bytes in length.		
Layer 3			
IPv4 routing	Wirespeed routing of IPv4 packets Up to 2K (2048) static routes and up to 256 IP interfaces		
Wirespeed IPv6 Static Routing	Up to 2K (2048) static routes and up to 128 IPv6 interfaces		
Layer 3 Interface	Configuration of layer 3 interface on physical port, LAG, VLAN interface or Loopback interface		
CIDR	Support for Classless Inter-Domain Routing		
RIP v2 (on 500X)	Support for Routing Information Protocol version 2, for dynamic routing		
VRRP (on 500X)	Virtual Router Redundancy Protocol (VRRP) delivers improved availability in a Layer 3 network by providing redundancy of the default gateway servicing hosts on the network. VRRP versions 2 and 3 are supported. Up to 255 virtual routers are supported.		
DHCP Server	Switch functions as an IPv4 DHCP Server serving IP addresses for multiple DHCP pools/scopes Support for DHCP options		
DHCP Relay at Layer 3	Relay of DHCP traffic across IP domains.		
User Datagram Protocol (UDP) Relay	Relay of broadcast information across Layer 3 domains for application discovery or relaying of BOOTP/DHCP packets.		

Feature	Description
Stacking	
Hardware stack	Up to 8 units in a stack. Up to 416 ports managed as a single system with hardware failover.
High availability	Fast stack failover delivers minimal traffic loss.
Plug-and-play stacking configuration/management	Master/backup for resilient stack control Auto-numbering Hot swap of units in stack Ring and chain stacking options Auto stacking port speed Flexible stacking port options
High-speed stack interconnects	Cost-effective 5G copper and high-speed 10G Fiber and Copper interfaces.
Hybrid stack	A mix of SF500, SG500, and SG500X in the same stack (10/100, Gigabit, and 10 Gigabit).
Security	
SSH	SSH is a secure replacement for Telnet traffic. SCP also uses SSH. SSH versions 1 and 2 are supported.
SSL	Secure Sockets Layer (SSL) encrypts all HTTPS traffic, allowing secure access to the browser-based management GUI in the switch.
IEEE 802.1X (Authenticator role)	RADIUS authentication and accounting, MD5 hash, guest VLAN, unauthenticated VLAN, single/multiple host mode and single/multiple sessions Supports time-based 802.1X Dynamic VLAN assignment
Web Based Authentication	Web based authentication provides network admission control through web browser to any host devices and operating systems.
STP BPDU Guard	A security mechanism to protect the networks from invalid configurations. A port enabled for Bridge Protocol Data Unit (BPDU) Guard is shut down if a BPDU message is received on that port. This avoids accidental topology loops.
STP Root Guard	This prevents edge devices not in the network administrator's control from becoming Spanning Tree Protocol root nodes.
DHCP snooping	Filters out DHCP messages with unregistered IP addresses and/or from unexpected or untrusted interfaces. This prevents rogue devices from behaving as a DHCP Server.
IP Source Guard (IPSG)	When IP Source Guard is enabled at a port, the switch filters out IP packets received from the port if the source IP addresses of the packets have not been statically configured or dynamically learned from DHCP snooping. This prevents IP Address Spoofing.
Dynamic ARP Inspection (DAI)	The switch discards ARP packets from a port if there are no static or dynamic IP/MAC bindings or if there is a discrepancy between the source or destination address in the ARP packet. This prevents man-in-the-middle attacks.
IP/Mac/Port Binding (IPMB)	The features (DHCP Snooping, IP Source Guard, and Dynamic ARP Inspection) above work together to prevent DoS attacks in the network, thereby increasing network availability
Secure Core Technology (SCT)	Ensures that the switch will receive and process management and protocol traffic no matter how much traffic is received.
Secure Sensitive Data (SSD)	A mechanism to manage sensitive data (such as passwords, keys, etc.) securely on the switch, populating this data to other devices, and secure autoconfig. Access to view the sensitive data as plaintext or encrypted is provided according to the user configured access level and the access method of the user.
Layer 2 isolation (PVE) with community VLAN	Private VLAN Edge provides security and isolation between switch ports, which helps ensure that users cannot snoop on other users' traffic; supports multiple uplinks.
Port security	Ability to lock Source MAC addresses to ports, and limit the number of learned MAC addresses.
RADIUS/TACACS+	Supports RADIUS and TACACS authentication. Switch functions as a client.
RADIUS accounting	The RADIUS accounting functions allow data to be sent at the start and end of services, indicating the amount of resources (such as time, packets, bytes, and so on) used during the session.
Storm control	Broadcast, multicast, and unknown unicast.
DoS prevention	Denial-of-Service (DoS) attack prevention.
Multiple user privilege levels in CLI	Levels 1, 7, and 15 privilege levels.
ACLs	Support for up to 2K (2048) rules on 500 Series and 3K (3072) on 500X series. Drop or rate limit based on source and destination MAC, VLAN ID or IP address, protocol, port, DSCP/IP precedence, TCP/User Datagram Protocol (UDP) source and destination ports, 802.1p priority, Ethernet type, Internet Control Message Protocol (ICMP) packets, Internet Group Management Protocol (IGMP) packets, TCP flag. Time-based ACLs supported.

Feature	Description
Quality of Service	
Priority levels	8 hardware queues
Scheduling	Strict Priority and weighted round-robin (WRR)
Class of service	Port based; 802.1p VLAN priority based; IPv4/v6 IP precedence/ToS/DSCP based; DiffServ; classification and re-marking ACLs, Trusted QoS Queue assignment based on differentiated services code point (DSCP) and class of service (802.1p/CoS)
Rate limiting	Ingress policer; egress shaping and ingress rate control; per VLAN, per port, and flow based
Congestion avoidance	A TCP congestion avoidance algorithm is required to minimize and prevent global TCP loss synchronization.
Standards	
Standards	IEEE 802.3 10BASE-T Ethernet, IEEE 802.3u 100BASE-TX Fast Ethernet, IEEE 802.3ab 1000BASE-T Gigabit Ethernet, IEEE 802.3ad Link Aggregation Control Protocol, IEEE 802.3z Gigabit Ethernet, IEEE 802.3x Flow Control, IEEE 802.3ad LACP, IEEE 802.1D (STP, GARP and GVRP), IEEE 802.1Q/p VLAN, IEEE 802.1w Rapid STP, IEEE 802.1s Multiple STP, IEEE 802.1X Port Access Authentication, IEEE 802.3af, IEEE 802.3at, RFC 768, RFC 783, RFC 791, RFC 792, RFC 793, RFC 813, RFC 879, RFC 896, RFC 826, RFC 854, RFC 855, RFC 856, RFC 858, RFC 894, RFC 919, RFC 922, RFC 920, RFC 950, RFC 951, RFC 1042, RFC 1071, RFC 1123, RFC 1141, RFC 1155, RFC 1157, RFC 1350, RFC 1533, RFC 1541, RFC 1542, RFC 1624, RFC 1700, RFC 1867, RFC 2030, RFC 2616, RFC 2131, RFC 2132, RFC 3164, RFC 3411, RFC 3412, RFC 3413, RFC 3414, RFC 3415, RFC 2576, RFC 4330, RFC 1213, RFC 1215, RFC 1286, RFC 1442, RFC 1451, RFC 1493, RFC 1573, RFC 1643, RFC 1757, RFC 1907, RFC 2011, RFC 2012, RFC 2013, RFC 2233, RFC 2618, RFC 2665, RFC 2666, RFC 2674, RFC 2737, RFC 2819, RFC 2863, RFC 1157, RFC 1493, RFC 1215, RFC 3416
IPv6	
IPv6	IPv6 Host Mode IPv6 over Ethernet Dual IPv6/IPv4 stack IPv6 Neighbor and Router Discovery (ND) IPv6 Stateless Address Autoconfiguration Path MTU Discovery Duplicate Address Detection (DAD) ICMPv6 IPv6 over IPv4 network with ISATAP tunnel support USGv6 and IPv6 Gold Logo certified
IPv6 QoS	Prioritize IPv6 packets in hardware
IPv6 ACL	Drop or Rate Limit IPv6 packets in hardware
IPv6 First Hop Security	RA guard ND inspection DHCPv6 guard Neighbor binding table (Snooping and static entries) Neighbor binding integrity check
Multicast Listener Discovery (MLD v1/2) snooping	Deliver IPv6 multicast packets only to the required receivers
IPv6 applications	Web/SSL, Telnet Server/SSH, Ping, Traceroute, SNMP, TFTP, SNMP, RADIUS, Syslog, DNS client, DHCP Client, DHCP Autoconfig, IPv6 DHCP Relay, TACACS
IPv6 RFC supported	RFC 4443 (which obsoletes RFC 2463) - ICMPv6 RFC 4291 (which obsoletes RFC 3513) - IPv6 Address Architecture RFC 4291 - IP Version 6 Addressing Architecture RFC 2460 - IPv6 Specification RFC 4861 (which obsoletes RFC 2461) - Neighbor Discovery for IPv6 RFC 4862 (which obsoletes RFC 2462) - IPv6 Stateless Address Auto-configuration RFC 1981 - Path MTU Discovery RFC 4007 - IPv6 Scoped Address Architecture RFC 3484 - Default address selection mechanism RFC 5214 (which obsoletes RFC 4214) - ISATAP tunneling RFC 4293 - MIB IPv6: Textual Conventions and General Group RFC 3595 - Textual Conventions for IPv6 Flow Label
Management	
Web user interface	Built-in switch configuration utility for easy browser-based device configuration (HTTP/HTTPS). Supports configuration, system dashboard, system maintenance and monitoring.
SNMP	SNMP versions 1, 2c, and 3 with support for traps, and SNMP v3 User-based Security Model (USM)
Standard MIBs	lldp-MIB lldpextdot1-MIB lldpextdot3-MIB
	rfc2665-MIB rfc2668-MIB rfc2737-MIB

Feature	Description	
	lldpextmed-MIB rfc2674-MIB rfc2575-MIB rfc2573-MIB rfc2233-MIB rfc2013-MIB rfc2012-MIB rfc2011-MIB RFC-1212 RFC-1215	rfc3621-MIB rfc4668-MIB rfc4670-MIB trunk-MIB tunnel-MIB udp-MIB draft-ietf-bridge-8021x-MIB draft-ietf-bridge-rstpmib-04-MIB draft-ietf-hubmib-etherif-mib-v3-00-MIB ianaaddrfamnumbers-MIB
Standard MIBs (continued)	SNMPv2-CONF SNMPv2-TC p-bridge-MIB q-bridge-MIB rfc1389-MIB rfc1493-MIB rfc1611-MIB rfc1612-MIB rfc1850-MIB rfc1907-MIB rfc2571-MIB rfc2572-MIB rfc2574-MIB rfc2576-MIB rfc2613-MIB	ianaifty-MIB ianaprot-MIB inet-address-MIB ip-forward-MIB ip-MIB RFC1155-SMI RFC1213-MIB SNMPv2-MIB SNMPv2-SMI SNMPv2-TM RMON-MIB rfc1724-MIB dcb-raj-DCBX-MIB-1108-MIB rfc1213-MIB rfc1757-MIB
Private MIBs	CISCOB-ldp-MIB CISCOB-brgmulticast-MIB CISCOB-bridgemibobjects-MIB CISCOB-bonjour-MIB CISCOB-dhcpcl-MIB CISCOB-MIB CISCOB-wrantomtaildrop-MIB CISCOB-traceroute-MIB CISCOB-telnet-MIB CISCOB-stormctrl-MIB CISCOBssh-MIB CISCOB-socket-MIB CISCOB-sntp-MIB CISCOB-smon-MIB CISCOB-phy-MIB CISCOB-multisessionterminal-MIB CISCOB-mri-MIB CISCOB-jumboframes-MIB CISCOB-gvrp-MIB CISCOB-endofmib-MIB CISCOB-dot1x-MIB CISCOB-deviceparams-MIB CISCOB-cli-MIB CISCOB-cdb-MIB CISCOB-brgmacswitch-MIB CISCOB-3sw2swtables-MIB CISCOB-smartPorts-MIB CISCOB-tbi-MIB CISCOB-macbaseprio-MIB CISCOB-env_mib-MIB CISCOB-policy-MIB	CISCOB-iprouter-MIB CISCOB-ipv6-MIB CISCOB-mnginf-MIB CISCOB-lcli-MIB CISCOBlocalization-MIB CISCOB-mcmngr-MIB CISCOB-mng-MIB CISCOB-physdescription-MIB CISCOB-PoE-MIB CISCOB-protectedport-MIB CISCOB-rmon-MIB CISCOB-rs232-MIB CISCOB-SecuritySuite-MIB CISCOB-snmplib-MIB CISCOB-specialbpdu-MIB CISCOB-banner-MIB CISCOB-syslog-MIB CISCOB-TcpSession-MIB CISCOB-traps-MIB CISCOB-trunk-MIB CISCOB-tuning-MIB CISCOB-tunnel-MIB CISCOB-udp-MIB CISCOB-vlan-MIB CISCOB-ipstdacl-MIB CISCOB-eee-MIB CISCOB-ssl-MIB CISCOB-digitalkeymanage-MIB CISCOB-qosclimib-MIB CISCOB-vrrp-MIB CISCOB-tbp-MIB

Feature	Description
	CISCOSB-sensor-MIB CISCOSB-aaa-MIB CISCOSB-application-MIB CISCOSB-bridgesecurity-MIB CISCOSB-copy-MIB CISCOSB-CpuCounters-MIB CISCOSB-Custom1BonjourService-MIB CISCOSB-dhcp-MIB
	CISCOSB-stack-MIB CISCOSMB-MIB CISCOSB-secsd-MIB CISCOSB-draft-ietf-entmib-sensor-MIB CISCOSB-draft-ietf-syslog-device-MIB CISCOSB-rfc2925-MIB CISCOSB-vrrpv3-MIB CISCO-SMI-MIB
Private MIBs (continued)	CISCOSB-dif-MIB CISCOSB-dnscl-MIB CISCOSB-embweb-MIB CISCOSB-fft-MIB CISCOSB-file-MIB CISCOSB-greeneth-MIB CISCOSB-interfaces-MIB CISCOSB-interfaces_recovery-MIB CISCOSB-ip-MIB
	CISCOSB-DebugCapabilities-MIB CISCOSB-CDP-MIB CISCOSB-vlanVoice-MIB CISCOSB-EVENTS-MIB CISCOSB-sysmng-MIB CISCOSB-sct-MIB CISCO-TC-MIB CISCO-VTP-MIB CISCO-CDP-MIB
RMON	Embedded RMON software agent supports 4 RMON groups (history, statistics, alarms, and events) for enhanced traffic management, monitoring, and analysis
IPv4 and IPv6 Dual Stack	Coexistence of both protocol stacks to ease migration
Firmware upgrade	<ul style="list-style-type: none"> • Web browser upgrade (HTTP/HTTPS) and TFTP and SCP • Upgrade can be initiated through console port as well • Dual images for resilient firmware upgrades
Port mirroring	Traffic on a port can be mirrored to another port for analysis with a network analyzer or RMON probe. Up to 8 source ports can be mirrored to one destination port.
VLAN mirroring	Traffic from a VLAN can be mirrored to a port for analysis with a network analyzer or RMON probe. Up to 8 source VLANs can be mirrored to one destination port.
DHCP (Options 12, 66, 67, 82, 129, and 150)	DHCP options facilitate tighter control from a central point (DHCP Server), to obtain IP address, auto configuration (with configuration file download), DHCP Relay, and host name.
Auto configuration with Secure Copy (SCP) file download	Enables secure mass deployment with protection of sensitive data.
Text-editable configs	Config files can be edited with a text editor and downloaded to another switch, facilitating easier mass deployment.
Smartports	Simplified configuration of QoS and security capabilities.
Auto Smartports	Automatically applies the intelligence delivered through the Smartports roles to the port based on the devices discovered over Cisco Discovery Protocol or LLDP-MED. This facilitates zero touch deployments.
Secure Copy (SCP)	Securely transfer files to and from the switch.
Textview CLI	Scriptable CLI. A full CLI as well as a menu CLI is supported.
Cloud Services	Support for Cisco Small Business and Cisco OnPlus.
Localization	Localization of GUI and documentation into multiple languages.
Login banner	Configurable multiple banners for web as well as CLI.
Time-based port operation	Link up or down based on user-defined schedule (when the port is administratively up).
Other management	Traceroute; single IP management; HTTP/HTTPS; SSH; RADIUS; port mirroring; TFTP upgrade; DHCP client; BOOTP; Simple Network Time Protocol (SNTP); Xmodem upgrade; cable diagnostics; Ping; syslog; Telnet client (SSH secure support); Automatic time settings from Management Station.
Green (Power Efficiency)	
Energy Detect	Automatically turns power off on Gigabit Ethernet RJ-45 port when detecting link down. Active mode is resumed without loss of any packets when the switch detects the link is up.
Cable length detection	Adjusts the signal strength based on the cable length. Reduces the power consumption for cable shorter than 10m. Supported on Gigabit Ethernet models.
EEE compliant (802.3az)	Supports IEEE 802.3az on all Gigabit copper ports.
Disable port LEDs	LEDs can be manually turned off to save on energy.

Feature	Description																																																												
General																																																													
Jumbo frames	Frame sizes up to 9K (9216) bytes. Supported on 10/100 and Gigabit Ethernet interfaces. The default MTU is 2K.																																																												
MAC table	16K (16384) MAC addresses.																																																												
Discovery																																																													
Bonjour	The switch advertises itself using the Bonjour protocol.																																																												
LLDP (802.1ab) with LLDP-MED extensions	Link Layer Discovery Protocol (LLDP) allows the switch to advertise its identification, configuration, and capabilities to neighboring devices that store the data in a MIB. LLDP-MED is an enhancement to LLDP that adds the extensions needed for IP phones.																																																												
Cisco Discovery Protocol (CDP)	The switch advertises itself using the Cisco Discovery Protocol (CDP). It also learns the connected device and its characteristics via CDP.																																																												
Product Specifications																																																													
Power over Ethernet (PoE)																																																													
IEEE 802.3af and 802.3at PoE delivered over any of the RJ-45 ports within the listed power budgets	Switches support 802.2af, 802.3at, and Cisco pre-standard (legacy) PoE. Maximum power of 30W to any 10/100 or Gigabit base port until the PoE budget for the switch is reached. The total power available for PoE per switch is:																																																												
	<table border="1"> <thead> <tr> <th>Model Name</th> <th>Power Dedicated to PoE</th> <th>Number of Ports That Support PoE</th> </tr> </thead> <tbody> <tr><td>SF500-24</td><td>N/A</td><td>0</td></tr> <tr><td>SF500-24P</td><td>180W</td><td>24</td></tr> <tr><td>SF500-24MP</td><td>375W</td><td>24</td></tr> <tr><td>SF500-48</td><td>N/A</td><td>0</td></tr> <tr><td>SF500-48P</td><td>375W</td><td>48</td></tr> <tr><td>SF500-48MP</td><td>740W</td><td>48</td></tr> <tr><td>SG500-28</td><td>N/A</td><td>0</td></tr> <tr><td>SG500-28P</td><td>180W</td><td>24</td></tr> <tr><td>SG500-28MPP</td><td>740W</td><td>24</td></tr> <tr><td>SG500-52</td><td>N/A</td><td>0</td></tr> <tr><td>SG500-52P</td><td>375W</td><td>48</td></tr> <tr><td>SG500-52MP</td><td>740W</td><td>48</td></tr> <tr><td>SG500X-24</td><td>N/A</td><td>0</td></tr> <tr><td>SG500X-24P</td><td>375W</td><td>24</td></tr> <tr><td>SG500X-24MPP</td><td>740W</td><td>24</td></tr> <tr><td>SG500X-48</td><td>N/A</td><td>0</td></tr> <tr><td>SG500X-48P</td><td>375W</td><td>48</td></tr> <tr><td>SG500-48MP</td><td>740W</td><td>48</td></tr> <tr><td>SG500XG-8F8T</td><td>N/A</td><td>0</td></tr> </tbody> </table>	Model Name	Power Dedicated to PoE	Number of Ports That Support PoE	SF500-24	N/A	0	SF500-24P	180W	24	SF500-24MP	375W	24	SF500-48	N/A	0	SF500-48P	375W	48	SF500-48MP	740W	48	SG500-28	N/A	0	SG500-28P	180W	24	SG500-28MPP	740W	24	SG500-52	N/A	0	SG500-52P	375W	48	SG500-52MP	740W	48	SG500X-24	N/A	0	SG500X-24P	375W	24	SG500X-24MPP	740W	24	SG500X-48	N/A	0	SG500X-48P	375W	48	SG500-48MP	740W	48	SG500XG-8F8T	N/A	0
	Model Name	Power Dedicated to PoE	Number of Ports That Support PoE																																																										
	SF500-24	N/A	0																																																										
	SF500-24P	180W	24																																																										
	SF500-24MP	375W	24																																																										
	SF500-48	N/A	0																																																										
	SF500-48P	375W	48																																																										
	SF500-48MP	740W	48																																																										
	SG500-28	N/A	0																																																										
	SG500-28P	180W	24																																																										
	SG500-28MPP	740W	24																																																										
	SG500-52	N/A	0																																																										
	SG500-52P	375W	48																																																										
	SG500-52MP	740W	48																																																										
	SG500X-24	N/A	0																																																										
	SG500X-24P	375W	24																																																										
	SG500X-24MPP	740W	24																																																										
	SG500X-48	N/A	0																																																										
	SG500X-48P	375W	48																																																										
SG500-48MP	740W	48																																																											
SG500XG-8F8T	N/A	0																																																											
Power consumption (worst case)	<table border="1"> <thead> <tr> <th>Model Name</th> <th>Green Power (mode)</th> <th>System Power Consumption</th> <th>Power Consumption (with PoE)</th> <th>Heat Dissipation (BTU/hr)</th> </tr> </thead> <tbody> <tr> <td>SF500-24</td> <td>Energy Detect</td> <td>110V=13.7W 220V=14.8W</td> <td>N/A</td> <td>46.5</td> </tr> <tr> <td>SF500-24P</td> <td>Energy Detect</td> <td>110V=26.1W 220V=27W</td> <td>110V=216W 220V=211W</td> <td>719.96</td> </tr> <tr> <td>SF500-24MP</td> <td>Energy Detect</td> <td>110V=39.31W 220V=39.79W</td> <td>110V=380W 220V=429.67W</td> <td>1466</td> </tr> <tr> <td>SF500-48</td> <td>Energy Detect</td> <td>110V=24.3W 220V=24.8W</td> <td>N/A</td> <td>77.9</td> </tr> </tbody> </table>	Model Name	Green Power (mode)	System Power Consumption	Power Consumption (with PoE)	Heat Dissipation (BTU/hr)	SF500-24	Energy Detect	110V=13.7W 220V=14.8W	N/A	46.5	SF500-24P	Energy Detect	110V=26.1W 220V=27W	110V=216W 220V=211W	719.96	SF500-24MP	Energy Detect	110V=39.31W 220V=39.79W	110V=380W 220V=429.67W	1466	SF500-48	Energy Detect	110V=24.3W 220V=24.8W	N/A	77.9																																			
	Model Name	Green Power (mode)	System Power Consumption	Power Consumption (with PoE)	Heat Dissipation (BTU/hr)																																																								
	SF500-24	Energy Detect	110V=13.7W 220V=14.8W	N/A	46.5																																																								
	SF500-24P	Energy Detect	110V=26.1W 220V=27W	110V=216W 220V=211W	719.96																																																								
	SF500-24MP	Energy Detect	110V=39.31W 220V=39.79W	110V=380W 220V=429.67W	1466																																																								
SF500-48	Energy Detect	110V=24.3W 220V=24.8W	N/A	77.9																																																									

Feature	Description				
	SF500-48P	Energy Detect	110V=46.8W 220V=47.5W	110V=437W 220V=429.5W	1465.51
	SF500-48MP	Energy Detect	110V=60.48W 220V=60.21W	110V=853.04W 220V=826.62W	2910
	SG500-28	EEE + Short Reach + Energy Detect	110V=23.2W 220V=23.6W	N/A	74.2
	SG500-28P	EEE + Short Reach + Energy Detect	110V=35W 220V=35.9W	110V=227W 220V=221.5W	755.79
	SG500-28MPP	EEE + Short Reach + Energy Detect	110V=40.38W 220V=41.0W	110V=803.6W 220V=808.6W	2729.06
	SG500-52	EEE + Short Reach + Energy Detect	110V=47W 220V=47W	N/A	147.7
	SG500-52P	EEE + Short Reach + Energy Detect	110V=63.7W 220V=64.7W	110V=460.5W 220V=452W	1542.29
	SG500-52MP	EEE + Short Reach + Energy Detect	110V=70.3W 220V=70.5W	110V=873.5W 220V=857.3W	2807.51
	SG500X-24	EEE + Short Reach + Energy Detect	110V=36.5W 220V=36.2W	N/A	114.7
	SG500X-24P	EEE + Short Reach + Energy Detect	110V=57.2W 220V=57.9W	110V=456W 220V=438W	1494.52
	SG500X-24MPP	EEE + Short Reach + Energy Detect	110V=64.75W 220V=65.13W	110V=851.08W 220V=825.91W	2904
	SG500X-48	EEE + Short Reach + Energy Detect	110V=60.3W 220V=60.3W	N/A	189.5
	SG500X-48P	EEE + Short Reach + Energy Detect	110V=74.4W 220V=75W	110V=474W 220V=462W	1576.41
	SG500X-48MP	EEE + Short Reach + Energy Detect	110V=87.33W 220V=85.43W	110V=880.75W 220V=855.13W	3006
	SG500XG-8F8T	EEE + Short Reach + Energy Detect	110V=93.7W 220V=94.33W	N/A	321.87
Ports	Model Name	Total System Ports	RJ-45 Ports	Combo Ports (RJ-45 + SFP)	
	SF500-24	24FE + 4 GE (5G Stacking)	24 FE	2 combo GE + 2 1G/5G SFP	
	SF500-24P	24FE + 4 GE (5G Stacking)	24 FE	2 combo GE + 2 1G/5G SFP	
	SF500-24MP	24FE + 4 GE (5G Stacking)	24 FE	2 combo GE + 2 1G/5G SFP	
	SF500-48	48FE + 4 GE (5G Stacking)	48 FE	2 combo GE + 2 1G/5G SFP	
	SF500-48P	48FE + 4 GE (5G Stacking)	48 FE	2 combo GE + 2 1G/5G SFP	
	SF500-48MP	48FE + 4 GE (5G Stacking)	48 FE	2 combo GE + 2 1G/5G SFP	
	SG500-28	24GE + 4 GE (5G Stacking)	24 GE	2 combo GE + 2 1G/5G SFP	
	SG500-28P	24GE + 4 GE (5G Stacking)	24 GE	2 combo GE + 2 1G/5G SFP	
	SG500-28MPP	24GE + 4 GE (5G Stacking)	24 GE	2 combo GE + 2 1G/5G SFP	
	SG500-52	48GE + 4 GE (5G Stacking)	48 GE	2 combo GE + 2 1G/5G SFP	
	SG500-52P	48GE + 4 GE (5G Stacking)	48 GE	2 combo GE + 2 1G/5G SFP	
	SG500-52MP	48GE + 4 GE (5G Stacking)	48 GE	2 combo GE + 2 1G/5G SFP	
	SG500X-24	24GE + 4 10GE	24 GE	4 XG SFP+ (Two combo 5G SFP slots)	
	SG500X-24P	24GE + 4 10GE	24 GE	4 XG SFP+ (Two combo 5G SFP slots)	

Feature	Description			
	SG500X-24MPP	24GE + 4 10GE	24 GE	4 XG SFP+ (Two combo 5G SFP slots)
	SG500X-48	48GE + 4 10GE	48 GE	4 XG SFP+ (Two combo 5G SFP slots)
	SG500X-48P	48GE + 4 10GE	48 GE	4 XG SFP+ (Two combo 5G SFP slots)
	SG500X-48MP	48GE + 4 10GE	48 GE	4 XG SFP+ (Two combo 5G SFP slots)
	SG500XG-8F8T	8 XG Copper + 8 XG SFP+ plus 1 GE Management	8 XG + 1 GE Mgmt	8 XG SFP+
Buttons	Reset button			
Cabling type	Unshielded twisted pair (UTP) Category 5 or better; Fiber options (SMF and MMF); Coaxial SFP+ for stacking purposes			
LEDs	LED power savings, System, Link/Act, PoE, Speed			
Flash	32 MB			
800 MHz ARM CPU memory	256 MB			
Packet buffer	All numbers are aggregate across all ports, as the buffers are dynamically shared:			
	Model Name	Packet Buffer		
	SF500-24	8Mb		
	SF500-24P	8Mb		
	SF500-24MP	8Mb		
	SF500-48	2 8Mb		
	SF500-48P	2 8Mb		
	SF500-48MP	2 8Mb		
	SG500-28	8Mb		
	SG500-28P	8Mb		
	SG500-28MPP	8Mb		
	SG500-52	2 8Mb		
	SG500-52P	2 8Mb		
	SG500-52MP	2 8Mb		
	SG500X-24	12Mb		
	SG500X-24P	12Mb		
	SG500X-24MPP	12Mb		
	SG500X-48	2 12Mb		
	SG500X-48P	2 12Mb		
	SG500X-48MP	2 12Mb		
	SG500XG-8F8T	16Mb		
Supported SFP/SFP+ Modules	SKU	Media	Speed	Maximum Distance
Note: Gigabit (MGBxxx) and 10-Gigabit (SFP-xxx) modules also work in the SG500XG-8F8T Ten Gigabit switch model.	MFEFX1	Multi-mode fiber	100 Mbps	2 km
	MFELX1	Single-mode fiber	100 Mbps	15 km
	MFEBX1	Single-mode fiber	100 Mbps	20 km
	MGBBX1	Single-mode fiber	1000 Mbps	10 km
	MGBSX1	Multi-mode fiber	1000 Mbps	500 m
	MGBLH1	Single-mode fiber	1000 Mbps	40 km
	MGBLX1	Single-mode fiber	1000 Mbps	10 km

Feature	Description			
	MGBT1	UPT cat 5	1000 Mbps	100 m
	SFP-H10GB-CU1M	Copper coax	5G (Sx500)/10G (SG500X)	1 m
	SFP-H10GB-CU3M	Copper coax	5G (Sx500)/10G (SG500X)	3 m
	SFP-H10GB-CU5M	Copper coax	5G (Sx500)/10G (SG500X)	5 m
	SFP-10G-SR	Multi-mode fiber	10 Gig	400 m
	SFP-10G-LR	Single-mode fiber	10 Gig	10 km
	SFP-10G-LRM	Single-mode/multi-mode fiber	10 Gig	300 m
Stack Connection Options				
	500		500X	
500	5G copper - SFP-H10GB-CUxM 1G fiber or copper - MGBxxx 1G Base-T - embedded RJ45 (S1/S2)		5G copper - SFP-H10GB-CUxM 1G fiber or copper - MGBxxx	
500X	5G copper - SFP-H10GB-CUxM 1G fiber or copper - MGBxxx		10G copper - SFP-H10GB-CUxM 10G Fiber - SFP-10G-xx 1G fiber or copper - MGBxxx	
Environmental				
Unit Dimensions (W x H x D)	Model Name		Unit Dimensions	
	SF500-24		440 x 44 x 257 mm	
	SF500-24P		440 x 44 x 257 mm	
	SF500-24MP		440 x 44 x 257 mm	
	SF500-48		440 x 44 x 257 mm	
	SF500-48P		440 x 44 x 350 mm	
	SF500-48MP		440 x 44 x 350 mm	
	SG500-28		440 x 44 x 257 mm	
	SG500-28P		440 x 44 x 257 mm	
	SG500-28MPP		440 x 44 x 350 mm	
	SG500-52		440 x 44 x 257 mm	
	SG500-52P		440 x 44 x 350 mm	
	SG500-52MP		440 x 44 x 350 mm	
	SG500X-24		440 x 44 x 257 mm	
	SG500X-24P		440 x 44 x 350 mm	
	SG500X-24MPP		440 x 44 x 350 mm	
	SG500X-48		440 x 44 x 257 mm	
	SG500X-48P		440 x 44 x 350 mm	
	SG500X-48MP		440 x 44 x 350 mm	
	SG500XG-8F8T		440 x 44 x 350 mm	
Unit weight	Model Name		Unit Weight	
	SF500-24		3.09 kg	
	SF500-24P		3.73 kg	
	SF500-24MP		4.35 kg	
	SF500-48		3.43 kg	
	SF500-48P		5.61 kg	
	SF500-48MP		5.52 kg	

Feature	Description			
	SG500-28	3.4 kg		
	SG500-28P	3.95 kg		
	SG500-28MPP	5.28 kg		
	SG500-52	3.95 kg		
	SG500-52P	5.61 kg		
	SG500-52MP	5.6 kg		
	SG500X-24	3.45 kg		
	SG500X-24P	5.25 kg		
	SG500X-24MPP	4.61 kg		
	SG500X-48	4.01 kg		
	SG500X-48P	5.74 kg		
	SG500X-48MP	5.43 kg		
	SG500XG-8F8T	5.25 kg		
Power	100-240V 47-63 Hz, internal, universal			
Certification	UL (UL 60950), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47) Class A			
Operating temperature	SF500-24, SF500-24P, SF500-48, SF500-48P, SG500-28, SG500-28P, SG500-52, SG500-52P, SG500X-24, SG500X-24P, SG500X-48, SG500X-48P 32°to 104°F (0°to 40°C) SG500-28MPP, SG500-52MP, SG500XG-8F8T, SF500-24MP, SF500-48MP, SG500X-24MPP, SG500X-48MP 32°to 122°F (0°to 50°C)			
Storage temperature	-4°to 158°F (-20°to 70°C)			
Operating humidity	10% to 90%, relative, noncondensing			
Storage humidity	10% to 90%, relative, noncondensing			
Acoustic noise and mean time between failures (MTBF)	Model Name	Fan (Number)	Acoustic Noise	MTBF @ 40°C (Hours)
	SF500-24	No fan	N/A	210,801.7
	SF500-24P	2 pcs/6300rpm No fan speed control	41 dB	260,626.2
	SF500-24MP	2pcs	44 dB	514157 (at 50C)
	SF500-48	No fan	N/A	131,127.2
	SF500-48P	3 pcs/9500rpm and fan speed control	30°C=43dB 40°C=54.5dB	147,998.3
	SF500-48MP	3 pcs	46.9 dB	322111 (at 50C)
	SG500-28	No fan	N/A	141,161.0
	SG500-28P	2 pcs/6300rpm No fan speed control	41.2 dB	253,175.1
	SG500-28MPP	2 pcs/6300rpm No fan speed control	41.2 dB	188,722 (at 50C)
	SG500-52	2 pcs/5000rpm No fan speed control	41.3dB	154,250.1
	SG500-52P	4 pcs/9500rpm and fan speed control	30°C=41.1dB 40°C=54.8dB	143,124.8
	SG500-52MP	4 pcs/9500rpm and fan speed control	30°C=41.1dB 40°C=54.8dB	186,968 (at 50C)
	SG500X-24	1 pcs/6300rpm No fan speed control	40.2dB	246,188.2
	SG500X-24P	3 pcs/9500rpm and fan speed control	30°C=40.1dB 40°C=52.2dB	132,225.7

Feature	Description			
	SG500X-24MPP	3pcs	46.4 dB	428,088 (at 50C)
	SG500X-48	2 pcs/5000rpm No fan speed control	41.1dB	166,796.4
	SG500X-48P	4 pcs/9500rpm and fan speed control	30°C=40.9dB 40°C=54.2dB	137,246.1
	SG500X-48MP	4 pcs	46.4 dB	307978 (at 50C)
	SG500XG-8F8T	4 pcs/9500rpm and fan speed control	30°C=41.7dB 40°C=55.3dB	131,290 (at 50C)
Warranty	Limited lifetime with next-business-day advance replacement (where available, otherwise same day ship)			

Package Contents
<ul style="list-style-type: none"> • Cisco Small Business 500/500X Series Stackable Managed Switch • Power cord • Mounting kit included with all models • Serial cable • CD-ROM with user documentation (PDF) included • Quick Start Guide
Minimum Requirements
<ul style="list-style-type: none"> • Web browser: Mozilla Firefox version 8 or later; Microsoft Internet Explorer version 7 or later, Safari, Chrome • Category 5 Ethernet network cable • TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed

Ordering Information

Table 2. Cisco 500 Series Switches Ordering Information

Model Name	Product Order ID Number	Description
Fast Ethernet		
SF500-24	SF500-24-K9	<ul style="list-style-type: none"> • 24 10/100 ports • 4 Gigabit Ethernet (2 combo[*] Gigabit Ethernet + 2 1GE/5GE SFP)
SF500-24P	SF500-24P-K9	<ul style="list-style-type: none"> • 24 10/100 PoE+ ports • 4 Gigabit Ethernet (2 combo[*] Gigabit Ethernet + 2 1GE/5GE SFP)
SF500-24MP	SF500-24MP-K9	<ul style="list-style-type: none"> • 24 10/100 POE+ ports with 370W power budget • 4 Gigabit Ethernet (2 combo Gigabit Ethernet + 2 1GE/5GE SFP)
SF500-48	SF500-48-K9	<ul style="list-style-type: none"> • 48 10/100 ports • 4 Gigabit Ethernet (2 combo[*] Gigabit Ethernet + 2 1GE/5GE SFP)
SF500-48P	SF500-48P-K9	<ul style="list-style-type: none"> • 48 10/100 PoE+ ports • 4 Gigabit Ethernet (2 combo[*] Gigabit Ethernet + 2 1GE/5GE SFP)
SF500-48MP	SF500-48MP-K9	<ul style="list-style-type: none"> • 48 10/100 POE+ ports with 740W power budget • 4 Gigabit Ethernet (2 combo Gigabit Ethernet + 2 1GE/5GE SFP)
Gigabit Ethernet		
SG500-28	SG500-28-K9	<ul style="list-style-type: none"> • 24 10/100/1000 ports • 4 Gigabit Ethernet (2 combo[*] Gigabit Ethernet + 2 1GE/5GE SFP)
SG500-28P	SG500-28P-K9	<ul style="list-style-type: none"> • 24 10/100/1000 PoE+ ports with 180W power budget • 4 Gigabit Ethernet (2 combo[*] Gigabit Ethernet+ 2 1GE/5GE SFP)
SG500-28MPP	SG500-28MPP-K9	<ul style="list-style-type: none"> • 24 10/100/1000 PoE+ ports with 740W power budget • 4 Gigabit Ethernet (2 combo[*] Gigabit Ethernet+ 2 1GE/5GE SFP)
SG500-52	SG500-52-K9	<ul style="list-style-type: none"> • 48 10/100/1000 ports • 4 Gigabit Ethernet (2 combo[*] Gigabit Ethernet + 2 1GE/5GE SFP)

Model Name	Product Order ID Number	Description
SG500-52P	SG500-52P-K9	<ul style="list-style-type: none"> • 48 10/100/1000 PoE+ ports with 375W power budget • 4 Gigabit Ethernet (2 combo + Gigabit Ethernet+ 2 1GE/5GE SFP)
SG500-52MP	SG500-52MP-K9	<ul style="list-style-type: none"> • 48 10/100/1000 PoE+ ports with 740W power budget • 4 Gigabit Ethernet (2 combo + Gigabit Ethernet+ 2 1GE/5GE SFP)
Gigabit Ethernet with 10 Gigabit Uplinks		
SG500X-24	SG500X-24-K9	<ul style="list-style-type: none"> • 24 10/100/1000 ports • 4 10 Gigabit Ethernet SFP+ (2 10 GE+ 2 10GE/5GE-Stacking Combo)
SG500X-24P	SG500X-24P-K9	<ul style="list-style-type: none"> • 24 10/100/1000 PoE+ ports with 375W power budget • 4 10 Gigabit Ethernet SFP+ (2 10 GE+ 2 10GE/5GE-Stacking Combo)
SG500X-24MPP	SG500X-24MPP-K9	<ul style="list-style-type: none"> • 24 10/100/1000 PoE+ ports with 740W power budget • 4 10 Gigabit Ethernet SFP+ (2 10 GE+ 2 10GE/5GE-Stacking Combo)
SG500X-48	SG500X-48-K9	<ul style="list-style-type: none"> • 48 10/100/1000 ports • 4 10 Gigabit Ethernet SFP+ (2 10 GE+ 2 10GE/5GE-Stacking Combo)
SG500X-48P	SG500X-48P-K9	<ul style="list-style-type: none"> • 48 10/100/1000 PoE+ ports with 375W power budget • 4 10 Gigabit Ethernet SFP+ (2 10 GE+ 2 10GE/5GE-Stacking Combo)
SG500X-48MP	SG500X-48MP-K9	<ul style="list-style-type: none"> • 48 10/100/1000 PoE+ ports with 740W power budget • 4 10 Gigabit Ethernet SFP+ (2 10 GE+ 2 10GE/5GE-Stacking Combo)
10 Gigabit Ethernet		
SG500XG-8F8T	SG500XG-8F8T-K9	<ul style="list-style-type: none"> • 8 10 Gigabit Ethernet 10GBase-T copper port • 8 10 Gigabit Ethernet SFP+ (dedicated) • 1 Gigabit Ethernet management port

