

DFX6024A



- For industrial and residential applications
- Wide input range: 100 - 240 Vac
- Flexible power continuity up to 67 W
- Protection class II
- Wide temperature range: -25 to 70°C
- Overload, overvoltage and short-circuit protection
- DIN Rail and wall mounted
- Extremely small size
- 3 years warranty

Input Data

Nominal input voltage range	100 – 240 Vac
AC input voltage range	85 – 264 Vac <i>(see Derating Curve)</i>
DC input voltage range	120 – 250 Vdc Connect N(+), L(-)
AC frequency range	47 – 63 Hz
Input current (approx.)	0.96 A (120 Vac) 0.57 A (230 Vac)
Inrush current (typ.)	≤ 20 A (≤ 5 ms)
Hold-up time	> 20 msec (120 Vac) > 80 msec (230 Vac)
Start-up delay (max.)	1 s
Internal fuse	T 2.5 A, slow-blow
External MCB (recommended)	6 A (curve B)

Output Data

Output voltage (factory setting)	24 Vdc ±3%
Output voltage range	22 – 29 Vdc
Output current at 24 Vdc	2.8 A <i>(see Derating Curve)</i>
Output power	67 W <i>(see Derating Curve)</i>
Maximum output current	6 A
Residual ripple	≤ 50 mV_{pp} (20 MHz, 50Ω)
Efficiency	≥ 85 %
Start-up with capacitive load	≤ 30.000µF
Over temperature protection	Shut-down and automatic restart
Overload protection	Continuous current mode
Short-circuit protection	Continuous current mode
Over voltage protection	Yes (typ. 35 Vdc)
Parallel connection	Yes
Series connection	Yes

Environment Data

Operational temperature	-25 to 70 °C <i>(see Derating Curve)</i>
Storage temperature	-40 to 85 °C
Operational humidity (25 °C)	≤ 90 %, no condensation

General Data

Insulation voltage (Input/Output)	3000 Vac
Protection class	II
Protection degree (EN 60529)	IP 20
Pollution degree	2
MTBF	> 500.000 h
Screw type connection	0.2 - 2.5 mm² (24 – 12 AWG) 0.6 - 0.8 Nm
Housing material	Polycarbonate
Foot latch material	Plastic POM
Dimension (WxHxD)	72 x 90 x 61 mm
Weight (approx.)	0.3 Kg

EMC

Noise immunity according to EN61000-6-2: EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6.
Emitted interference according to EN61000-6-3: class B for industrial and residential area.

Certification

CE mark according to EMC 2014/30/UE and Low Voltage Directive 2014/35/UE.

Standards

EN 60204-1, EN 60950-1, EN 50178, ANSI/ISA-12.12.01 Class I Division 2

Approvals (Pending)

UL 508, UL 60950, UL 1310 (NEC Class 2)

Derating Curves

