



DISTRIBUTION BOARD

GTA 228-KT-t



GTA 228-KT-t

Distribution board

CUSTOMIZE

320 x 320 x 179 mm
Article number: 01622801

Automatic machine enclosure - Industrial Quality -, 2-row, PE/N terminal, with each 2 clamping points 16 mm², 10 clamping points 6 mm², masking and labelling strips, 3 x housing connectors (GGV)

with transparent hinged door



Technical data

Measures

Width:	320 mm
Length:	320 mm
Height:	179 mm
Inner height:	157 mm

Material:

Box:	polycarbonate, glass fiber-reinforced
Cover:	Polycarbonate
Sealing:	Polyurethane
Cover screw:	Polyamide 6, fiber-glass reinforced
material:	Polycarbonate

Environmental attributes

Max. rel. humidity at 25° C (short term):	95%
Max. rel. humidity at 40° C:	50%
Ambient temperature (24 h):	35 °C
Ambient temperature (max.):	40 °C
Ambient temperature (min.):	-25 °C



DISTRIBUTION BOARD

GTA 228-KT-t

Other attributes

Color:	Grey
Number of distribution units:	14
Tackable:	Yes
Functional integrity:	none
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Protection class:	II
Rated insulation voltage AC:	400 V
Ingress protection:	IP65 - acc. to EN 60529 / DIN VDE 0470-1
weatherproof:	Yes
Cover screw torque:	2.5 N m