

PRODUCT DATASHEET

HALOSPOT 111 35 W 12 V 24° G53

HALOSPOT® 111 | Halogen spot lamps with 111 mm aluminum reflector



Areas of application

- General illumination
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings
- Entrance lighting

Product benefits

- Brilliant accent light
- Cap for reduced glare and ease of handling
- Burner with axial filament for optimum distribution of light
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Drastically reduced thermal load in luminaire thanks to aluminum-coated reflector
- Contains no mercury

Product features

- Average life: 4,000 h
- 100 % dimmable
- Color rendering index R_a : 100
- Diameter: 111 mm


TECHNICAL DATA

Electrical data

| | |
|----------------------|---------|
| Nominal wattage | 35 W |
| Construction wattage | 35.00 W |
| Nominal voltage | 12 V |

Photometrical data

| | |
|---------------------------|------------|
| Luminous intensity | 2500 cd |
| Luminous efficacy | lm/W |
| Light color (designation) | Warm White |
| Color temperature | 2900 K |
| Color rendering index Ra | 100 |
| Light color | 1029 |
| UV protection | Yes |



Light technical data

| | |
|---------------|------|
| Beam angle | 24 ° |
| Starting time | 0 s |

Dimensions & Weight

| | |
|----------------|----------|
| Overall length | 60.00 mm |
| Diameter | 111,0 mm |
| Product weight | 51.67 g |

Lifespan

| | |
|------------------------|--------|
| Nominal lamp life time | 4000 h |
|------------------------|--------|

Additional product data

| | |
|-----------------------------|-----------|
| Base (standard designation) | G53 |
| Mercury-free | Yes |
| Design / version | Reflector |

| | |
|----------------|--|
| Product remark | If connectors are used, an additional holder is required at the rim of the reflector / May produce noise in combination with some dimmers. Recommended solution: use OSRAM HTi DALI 150/230-240 DIM with OSRAM DALI MCU |
|----------------|--|

Capabilities

| | |
|------------------|-----|
| Dimmable | Yes |
| Burning position | Any |

Country-specific categorizations

| | |
|-----------------|---------------------------|
| ILCOS | HMGS//UB-35-12-G53-111/24 |
| Order reference | 41832 FL |

Energy labelling regulation data acc EU 2019/2015

| | |
|---|----------|
| Light source cap-type (or other electric interface) | G53 |
| Length | 67.00 mm |
| Height | 111,0 mm |
| Width | 111,0 mm |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4050300335766 | Folding box 1 | 86 mm x 87 mm x 112 mm | 82.67 g | 0.84 dm ³ |
| 4050300335773 | Shipping box 6 | 275 mm x 130 mm x 185 mm | 625.20 g | 6.61 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.