



CEILING JUNCTION BOX

**U 71 K DVD-3**

**U 71 K DVD-3**

**Ceiling junction box**

71 x 71 x 81 mm

Article number: 97186601

Ceiling connection box for installation in concrete, 4 screw bosses with 60 mm screw spacing, with M5 threaded bush to take a ceiling hook, combinable with a standard spacing of 71 mm, Fully insulated cable transition, suitable for opposing formwork, VDE certified as per DIN EN 60670 (VDE 0606)

3-part, with smooth face for nail and adhesive fixing



**Technical data**

**Measures**

Width:	71 mm
Length:	71 mm
Height:	81 mm

**Material:**

Box:	Polypropylen, Copolymer
Cover:	Polypropylen, Copolymer
material:	Polypropylene

**Entries**

Possible conduit entry points:	6 x bis Ø 25 mm, 2 x bis Ø 20 mm
--------------------------------	----------------------------------

**Accessory**

- KR - Adhesive blank
- ANSW - Weld screw
- DH 75-M5 - ceiling hook
- ES-10 - Installation screw
- ES-18 - Installation screw
- ES-25 - Installation screw
- IBT LZA-18 - Hole punch
- IBT LZA-23 - Hole punch
- IBT LZA-OE - Hole punch
- IBT ST - Plug
- IBT STE-LST/14 - Punch set
- IBT STE-LST/18 - Punch set
- IBT STE-LST/23 - Punch set
- IBT STE-LST/30 - Punch set
- IBT STE-LST/39 - Punch set
- IBT STE-LZA/10 - Punch set



CEILING JUNCTION BOX

# U 71 K DVD-3

## Other attributes

Color:	miscellaneous
Equipment:	None
sealable:	No
Rated insulation voltage AC:	450 V
Explosion safety:	none
Functional integrity:	none
Entries:	2
Tackable:	No
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP30 - acc. EN 60529 / DIN VDE 0470-1
weatherproof:	Yes

## Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 40° C:	50%
Max. rel. humidity at 25° C (short term):	-