



Main

Range	ARGUS
Product or component type	Movement detector
Load type	Incandescent lamp : 1000 W - 230 V AC Halogen lamp : 1000 W - 230 V AC Low voltage halogen lamp with wire-wound transformer : 500 VA Low voltage halogen lamp with electronic transformer : 250 VA Fluorescent tube : 200 VA - 230 V AC Compact fluorescent lamp : 3 x 23 W - 230 V AC Capacitive : : 6 A, 21 µF - 230 V AC Capacitive : : 10 A, 14 µF - 230 V AC
Colour tint	White
Type of packing	Blister

Complementary

[Ue] rated operational voltage	220...240 V
Network frequency	50 Hz
[Ue] rated operational voltage	220...240 V
Output current	10 A
Type of setting	Light sensitivity adjustable Time adjustment
Time delay	5 s...10 min
Light intensity adjustment	5...2000 lux
Horizontal detection angle	0...360 °
Detection face	Radius 3.9 m
Material	ABS + PC with matt surface
Device mounting	Ceiling
Mounting height	3 m

Environment

Condition of use	Indoor use only
IP degree of protection	IP20
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1737 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Available End of life manual