

Basic Wallbox Series - CCL-WBM

Type	CCL-WBM	
Code	490072	
Number of sockets	1	
Input		
AC power supply *	1P + N + PE	3P + N + PE
AC Voltage	230AC +/- 10%	400 V AC +/- 10%
Nominal input current **	32 A	32 A
Nominal input power	7,2 k	21 kW
Required power supply capacity	7,2 kVA	21 kVA
Frequency	50 / 60 Hz	50 / 60 Hz
Output		
Maximum output power	7,2 kW	21 kW
Maximum output current	32 A	32 A
AC output voltage	230 V AC +/- 10%	400 V AC +/- 10%
Charge system		
Socket A	Mode 3 (IEC 61851) Type 2 (UNE EN 62196-1)	
Socket B	-	
General		
Cable lenght	-	
Enclosure rating	IP 54 / IK 10	
Enclosure material	ABS plastic	
Installation mode	Simple installation, 4-point wallfixing	
Power limit control	Mode 3 PWM control according ISO/IEC 61851-1	
Operating temperature	-10 to +45 °C	
Operating humidity	To 95% RH Non-condensing	
Light beacon	Three color led status	
Net weight	4 Kg	
Optional devices		
Extended Temperature range	Heater (-30 to + 45 °C)	
Tethered cable	Type 2 (5 meters length)	
* depending on local installation		
**power limit control by software		

