



Main

| | |
|---------------------------|---------------|
| Range | Thorsman |
| Product or component type | Test meter |
| Supply | 2 battery 3 V |

Complementary

| | |
|----------------------|---|
| Display digits | 3.5 |
| Type of setting | Automatic reset |
| Signaling function | Low battery by visual |
| Function available | Audible continuity High precision measuring Tactile barrier for safety Data hold function |
| Type of measurement | Voltage DC: 200mV/2/20/200/600 V Resistance: 200 Ohm/2/20/200 kOhm/20 MOhm Voltage AC: 2/20/200/600 V Current AC: 2/20/200/600 A Continuity: < 30 Ohm Diode check: 1.5 V |
| Measurement category | Category III 600 V |
| Language | Spanish Hungarian German Portuguese French Polish |
| Height | 190 mm |
| Width | 76 mm |
| Depth | 36 mm |
| Net weight | 160 g with battery |

Environment

| | |
|-----------|-----------|
| Standards | IEC 61010 |
|-----------|-----------|

Offer Sustainability

| | |
|--------------------|-----------------------------------|
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Under investigation |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|