


Data sheet | Item number: 221-613

COMPACT Splicing Connectors; 3-conductor connector; with operating levers; Max.ambient operating temp. 85 °C

www.wago.com/221-613



Data

Electrical data



Ratings per IEC/EN 60664-1

Ratings per	EN 60664
Rated voltage (II / 2)	450 V
Rated impulse voltage (II / 2)	4 kV
Rated current	41 A
Legend (ratings)	(II / 2) Δ Overvoltage category II / Pollution degree 2

Connection data

Connection technology	CAGE CLAMP®
Actuation type	Lever
Connectable conductor materials	Copper
Nominal cross section	6 mm ²
Solid conductor	0.5 ... 6 mm ² / 20 ... 10 AWG
Stranded conductor	0.5 ... 6 mm ² / 20 ... 10 AWG
Fine-stranded conductor	0.5 ... 6 mm ² / 20 ... 10 AWG
Strip length	12 ... 14 mm / 0.47 ... 0.55 Inch
Total number of connection points	3
Total number of potentials	1
Type of wiring	Side-entry wiring

Geometrical Data

Width	22.9 mm / 0.902 Inch
Height	10.1 mm / 0.398 Inch
Depth	21.1 mm / 0.831 Inch

Material Data

Color	transparent
Flammability class per UL94	V2
Weight	4.014 g

Environmental Requirements

Surrounding air (operating) temperature	85 °C
Continuous operating temperature up to	105 °C
T-Marking per EN 60998	T85


Commercial data

Country of origin	DE
GTIN	4055143715416
Customs Tariff No.	85369010000

Country specific Approvals

Logo	Approval	Certificate name
	KEMA/KEUR DEKRA Certification B.V.	71-101850

Ship Approvals

Logo	Approval	Certificate name
	LR Lloyds Register	04/20013 (E6)

Subject to changes.

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.