

# Unmanaged 10/100Mbps PoE+ Switch

MODEL: TL-SL1218MP/TL-SL1218P/TL-SL1226P



## Highlights

- (For TL-SL1218P) 16 PoE+ 10/100 Mbps RJ45 ports, 2 Gigabit RJ45 ports and 1 combo Gigabit SFP slot
- (For TL-SL1218MP/TL-SL1226P) 16/24 PoE+ 10/100 Mbps RJ45 ports, 2 Gigabit RJ45 ports and 2 combo Gigabit SFP slots
- High PoE power budget with up to 30 W\* for each PoE port, and a total power budget of 150 W\* (for TL-SL1218P)/250 W\* (for TL-SL1218MP and TL-SL1226P)
- Up to 250 m data and power transmission under Extend Mode\*\* specially designed for surveillance system
- Priority mode for port 1–8 to guarantee the quality of sensitive applications like video monitor
- Isolation Mode allows one-click client traffic separation for higher security and performance
- Easy to use, with no configuration and installation needed

## Overview

TP-Link's new PoE/PoE+ switches with all 10/100 Mbps RJ45 ports supporting the PoE+ standard provides a simple way to expand the wired network while transferring power over the same ethernet cable at the same time. With up to 30 W\* per port, the switch can power more high-powered devices such as Access Points, IP Cameras, IP Phones and so on. Moreover, with innovative Extend Mode, devices can get PoE power supply and data transmission from a distance of 250 m\*\*. Priority mode ensures high priority for port 1–8, which guarantees the quality of sensitive applications. Moreover, the switch supports Isolation Mode that divides traffic for 10/100 Mbps RJ45 ports for higher security and performance.

## Power over Ethernet

- (For TL-SL1218P) Features 16 802.3af/at compliant PoE+ ports, with a total PoE power budget of 150 W\*
- (For TL-SL1218MP/TL-SL1226P) Features 16/24 802.3af/at compliant PoE+ ports, with a total PoE power budget of 250 W\*
- Flexible deployment for PoE supported devices such as wireless access points, IP Phones and IP Cameras
- Designed to use a single Ethernet cable for both data and power transmission, lowering infrastructure costs

## Highlight Performance



- Up to 250 m PoE power supply and data transmission under Extend Mode\*\*.
- After turning on the Priority Mode, there will be designated high priority ports for quality-sensitive application like Surveillance Video.
- Isolation Mode easily divides traffic for 10/100 Mbps RJ45 ports to avoid snooping and tampering, which improves LAN security and performance.

## Easy to Use

- Plug & play, no configuration required
- Auto MDI/MDIX eliminates the need for crossover cables
- Auto-negotiation intelligently adjusts for compatibility and optimal performance

# Specifications

## Hardware Features & Performance

Product Picture				
Model		TL-SL1218MP	TL-SL1218P	TL-SL1226P
General	Interfaces	16 10/100 Mbps RJ45 Ports	16 10/100 Mbps RJ45 Ports	24 10/100 Mbps RJ45 Ports
		2 10/100/1000 Mbps RJ45 Ports	2 10/100/1000 Mbps RJ45 Ports	2 10/100/1000 Mbps RJ45 Ports
		2 Combo Gigabit SFP Slots	1 Combo Gigabit SFP Slot	2 Combo Gigabit SFP Slots
PoE	PoE Standard	802.3af/at		
	PoE Ports	16, up to 30 W per port		24, up to 30 W per port
	PoE Power Budget	250 W	150 W	250 W
Performance	Switching Capacity	7.2 Gbps		8.8 Gbps
	Packet Forwarding Rate	5.36 Mpps		6.54 Mpps
	MAC Address Table	8 K		
	Packet Buffer	4.1 Mbit		
	Jumbo Frame	10 KB		
Advanced Features		Extend Mode (Up to 250 m PoE supply and data transmission)		
		Priority Mode		
		Isolation Mode		
Physical & Environment	Power Supply	100–240 V AC, 50/60 Hz		
	Max Power Consumption	285.8 W (with 250 W PD Connected) 14.97 W (no PD Connected)	172.8 W (with 250 W PD Connected) 12.71 W (no PD Connected)	281 W (with 250 W PD Connected) 17.17 W (no PD Connected)
	Max Heat Dissipation	974.58 BTU/h (with 250 W PD Connected) 51.05 BTU/h (no PD Connected)	589.25 BTU/h (with 250 W PD Connected) 43.34 BTU/h (no PD Connected)	958.21 BTU/h (with 250 W PD Connected) 58.55 BTU/h (no PD Connected)
	Dimensions (W × D × H)	17.3 × 7.1 × 1.7 in.(440 × 180 × 44 mm)		
	Fan Quantity	2		
	Operating Temperature	0 °C–50 °C (32 °F–122 °F)		
	Storage Temperature	-40 °C–70 °C (-40 °F–158 °F)		
	Operating Humidity	10%–90%RH non-condensing		
	Storage Humidity	5%–90%RH non-condensing		
	Certification	CE, FCC		

Note:

\* PoE budget calculations are based on laboratory testing. Actual PoE power budget is not guaranteed and will vary as a result of client limitations and environmental factors.

\*\*The speed of the ports which are under extend mode will be downgraded to 10Mbps. Actual transmission distance may vary from the quality of the cables.

Specifications are subject to change without notice. TP-Link is a registered trademark of TP-Link Technologies Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. Copyright © 2020 TP-Link Technologies Co., Ltd. All rights reserved.