



TERMINAL BLOCK ENCLOSURE

RK 4/12-12x4²



RK 4/12-12x4²

Terminal block enclosure

CUSTOMIZE

130 x 130 x 75 mm

Article number: 61501201

Terminal block enclosure, Polystyrene, light grey, similar to RAL 7035, incl. 4 attachment bushes M20, seal range 8 - 13.5 mm, IP54, 1 attachment bush M25, seal range 9 - 18.5 mm, IP54

with 12 screw terminals 4 mm², (type Weidmüller WDU 4)



Technical data

Measures

Width:	130 mm
Length:	130 mm
Height:	75 mm

Material:

Box:	Polystyrene, light grey, similar to RAL 7035
Cover:	Polystyrene, light grey, similar to RAL 7035
Sealing:	Polyurethane
Cover screw:	Polyamide 6, fiber-glass reinforced
material:	polystyrene

Accessory

ASS-kl - External hinge set

KS M25-gro - Combi set

HBA - Mounting material

KS M20 - Combi set

KS M25 - Combi set

KS M32 - Combi set

TK ABL - External fixing lugs kit

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short term):	95%
Max. rel. humidity at 40° C:	50%



TERMINAL BLOCK ENCLOSURE

RK 4/12-12x4²

Other attributes

Ingress protection:	IP66/IP54 - acc. EN60529 / DIN VDE 0470-1
Impact resistance:	IK07 acc. DIN EN 5012 / VDE 0470 Part 100
Protection class:	II - isolate protection acc. VDE 0106
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Combustion behaviour acc. to UL 94:	HB acc. UL94
Combustion behaviour acc. to VDE:	650°C acc. VDE 0471/ EN 60695
Fitted for outdoor application:	No
Cable entries:	Yes
sealable:	Yes
weatherproof:	No
Equiqment:	screw terminals
Number terminals:	12 Quantity
Rated cross section:	4 mm ²