



EMPTY ENCLOSURE

AKL 4-gh



AKL 4-gh

Empty enclosure

CUSTOMIZE

300 x 600 x 209 mm
Article number: 74290401

Empty enclosure, With double membrane seals, Sealing and insulating plugs, Base and cover: polystyrene, light grey similar to RAL 7035



Technical data

Measures

Width:	300 mm
Length:	600 mm
Height:	209 mm
Inner height:	191 mm

Material:

Box:	Polystyrene, light grey, similar to RAL 7035
Cover:	Polystyrene, light grey, similar to RAL 7035
Sealing:	Polyurethane
Cover screw:	Polyamide 6, fiber-glass reinforced
material:	polystyrene

Accessory

AK ABF 2 - Enclosure wall smooth

AK ABL-ES - External fixing lugs

AK MPI 4 - Mounting plate

AK NS35-250 - Standard rail

AK NS35-556 - Standard rail

AK TW - Partition wall

ASS-gro - External hinge set

NS35-216/3 - Standard rail

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short term):	95%
Max. rel. humidity at 40° C:	50%



EMPTY ENCLOSURE

AKL 4-gh

Other attributes

Ingress protection:	IP65 - acc. to EN 60529 / DIN VDE 0470-1
Impact resistance:	IK07 acc. DIN EN 5012 / VDE 0470 Part 100
Rated insulation voltage DC:	1000 V
PVC-free:	Yes
Heavy metals-free:	Yes
Silicone-free:	Yes
Combustion behaviour acc. to UL 94:	HB acc. UL94
Combustion behaviour acc. to VDE:	650°C acc. VDE 0471/ EN 60695
Cable entries:	Yes
Rated insulation voltage AC:	690 V
sealable:	Yes