



JUNCTION BOX

Abox-i 040-4²/sw

Abox-i 040-4²/sw


Junction box

CUSTOMIZE

93 x 93 x 55 mm
Article number: 49140401

Junction box - Industrial Quality - acc. to DIN EN 60670 (VDE 0606), Ui=690V, weatherproof, shock-proof, halogen-free, with self-sealing, soft inlet membranes, M20, seal range 2 - 16 mm

Black, with screw terminal, 5-pole - 2.5/4 mm² (4 x 1.5² / 4 x 2.5² / 3 x 4²)



Technical data

Measures

Width:	93 mm
Length:	93 mm
Height:	55 mm

Material:

Cover screw:	stainless steel V2A
Sealing:	thermoplastic elastomer
Box:	ASA-PC, membranes made from TPE
Cover:	ASA-PC
material:	ASA-PC

Certificates



Accessory

- KVR M20-GDB/MGM/sw - Cable gland
- WNI M20/sw - Twist nipple
- WST M20/sw - Twist plug
- Abox 025/040 KLS-2,5²/4² - Terminal block
- BST M20/sw - Ventilation seal
- Abox PST - Sealing kit
- BST M20 - Ventilation seal



JUNCTION BOX

Abox-i 040-4²/sw

Entries

Pre-embossings, top:	2 x M20
Pre-embossings, left/right:	2 x M20
Pre-embossings, bottom:	1 x M20
Pre-embossings, rear side:	1 x M20

Other attributes

Entries:	8
Rated cross section:	4 mm ²
Tackable:	No
Rated insulation voltage AC:	690 V
Explosion safety:	none
Functional integrity:	none
sealable:	Yes
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP65 - acc. to EN 60529 / DIN VDE 0470-1
weatherproof:	Yes
Combustion behaviour acc. to UL 94:	HB acc. UL94
Combustion behaviour acc. to VDE:	750°C acc. VDE 0471/ EN 60695
Equioment:	Terminal
Color:	black
Cover screw torque:	1.7 N m

Environmental attributes

Ambient temperature (24 h):	60 °C
Ambient temperature (max.):	80 °C
Ambient temperature (min.):	-35 °C
Max. rel. humidity at 25° C (short term):	95%
Max. rel. humidity at 40° C:	50%