

## Data sheet

### 050TMG


Yellow steady light module



## Features

|                   |                                             |
|-------------------|---------------------------------------------|
| Range             | 050 Control Cabinet Signalling and Lighting |
| Product           | Modular signal towers                       |
| Type              | Steady light modules                        |
| Item code         | 050TMG                                      |
| Description       | Yellow steady light module                  |
| Colour            | Yellow                                      |
| Weight - gr       | 130,000                                     |
| Custom tariff no. | 85365080                                    |

## Technical drawings



## Technical data

|                           |                                                    |
|---------------------------|----------------------------------------------------|
| Approvals                 | CE                                                 |
| Compliance with standards | EN-IEC60947-1, EN-IEC60947-5-1                     |
| Operating temperatures    | -25° ÷ +65°C                                       |
| Protection degree         | IP44 (EN-IEC60529)                                 |
| Protection against impact | IK07 (EN-IEC62262)                                 |
| Housing material          | PC Polycarbonate                                   |
| Combustion behaviour      | V0 (UL94)                                          |
| Terminal screws           | Tightening torque 0.8÷1 Nm                         |
| Terminal screws           | Comb.head screw:flat blade and Ph2 -Tool D.5mm max |
| Terminal screws material  | Zinc plated steel                                  |
| Bulb type                 | Ba15d 250V AC-DC 10W max (not included)            |
| Rated insulation voltage  | Ui 690V - Uimp 4KV (EN-IEC 60947-1)                |
| Overtoltage category      | Class II (EN-IEC 61140)                            |
| Signalling type           | Steady - Up to 5 modules                           |
| Assembly style            | 050TBA + 050TM + 050TA or 050TP                    |
| Warranty period           | 18 months                                          |