



LARGE CONDUIT BOX

U 120 K GRO-3

U 120 K GRO-3

Large conduit box

122 mm

Article number: 97371301

Large conduit ceiling socket for installation in concrete, for slab ceilings up to 6.5 cm thickness, with M5 threaded bush to take a ceiling hook, Lamp output halogen max. 6.5 W, Lamp output LED max. 3 W

3-part, with smooth face for nail and adhesive fixing



Technical data

Measures

Height: 122 mm

Material:

Box: Polypropylen, Copolymer

Cover: Polypropylen, Copolymer

material: Polypropylene

Entries

Possible conduit entry points: 4 x bis Ø 35 mm, 8 x bis Ø 26 mm

Accessory

ANSW - Weld screw

DH 115-M5 - ceiling hook

ES-10 - Installation screw

ES-18 - Installation screw

ES-25 - Installation screw

HW VD-67 - sealing cap

IBT LZA-18 - Hole punch

IBT LZA-23 - Hole punch

IBT LZA-OE - Hole punch

IBT STE-LST/14 - Punch set

IBT STE-LST/18 - Punch set

IBT STE-LST/23 - Punch set

IBT STE-LST/30 - Punch set

IBT STE-LST/39 - Punch set

IBT STE-LZA/10 - Punch set

IBT STE-LZA/14 - Punch set



LARGE CONDUIT BOX

U 120 K GRO-3

Other attributes

Color:	miscellaneous
Equipment:	None
sealable:	No
Rated insulation voltage AC:	450 V
Explosion safety:	none
Functional integrity:	none
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP30 - acc. EN 60529 / DIN VDE 0470-1
weatherproof:	Yes

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 40° C:	50%
Max. rel. humidity at 25° C (short term):	-