



SMALL-SCALE DISTRIBUTORS

AKi 12



AKi 12

Small-scale distributors

CUSTOMIZE

250 x 200 x 122 mm
Article number: 73641201

Small-scale distributors - Industrial Quality -, 12 distribution units, PE/N terminal, with each 2 clamping points 16 mm², 10 clamping points 6 mm², 8 elastic entries on top, masking and labelling strips, insulating seals, additional double-membrane seals



Technical data

Measures

Width:	250 mm
Length:	200 mm
Height:	122 mm

Material:

Box:	Polycarbonate, glass fibre reinforced, grey similar to RAL 7035
Cover:	Polycarbonate, glass fibre reinforced, grey similar to RAL 7035
Sealing:	Polyurethane
Cover screw:	Polyamide 6, fiber-glass reinforced
material:	Polycarbonate
Hinged window:	Polycarbonate,

Highlights

Easy to install - PE/N terminal strip, flexible entries on the top and the generous spacing of the strip allow for especially convenient, rapid installation of the distributors.

Reliable - The high protection class (IP65) and the robust, halogen-free design ensure reliable operation even in a tough industrial environment.

Accessory

- BST M20 - Ventilation seal
- BST M20/sw - Ventilation seal
- AK SGA-1 - Lock fittings

Environmental attributes

Ambient temperature (24 h):	60 °C
Ambient temperature (max.):	80 °C
Ambient temperature (min.):	-35 °C
Max. rel. humidity at 25° C (short term):	95%
Max. rel. humidity at 40° C:	50%



SMALL-SCALE DISTRIBUTORS

AKi 12

transparent

Other attributes

Color:	Grey
Ingress protection:	IP65 - acc. to EN 60529 / DIN VDE 0470-1
Number of distribution units:	12
Tackable:	Yes
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
sealable:	Yes
Impact resistance:	IK08 acc. DIN EN 5012 / VDE 0470 segment 100
Cover screw torque:	1.2 N m