

ADV SERIES

TYPHOON BIFLUX 25/35 G-PROT

DDF115.035.PLA.03.00



CONSUMABILI TORCIA PL-25C
ПЛАЗМОТРОН PL-25C РАСХОДНЫЕ МАТЕРИАЛЫ



PROCESSI / ПРОЦЕССЫ	EXTERNAL	BUILT - IN
Ciclo di lavoro Plasma • Рабочий цикл плазмы	35 A – 25%	25 A – 35%
Corrente al 100 % • Plasma output at 100% duty cycle	20 A	20 A

INVERTER / ИНВЕРТОР	EXTERNAL	BUILT - IN
Tensione di alimentazione • Поддача напряжения	230V±10%	230V±10%
Frequenza • Частота	50/60Hz	50/60Hz
Tensione a vuoto • Напряжение холостого хода	270 V	270 V
Potenza nominale Plasma 100% • Потр. мощность при плазме 100%	2,2 KW	2,4 KW
Tensione d'arco plasma • Напря-е дуги при св-ке плазмой	86 - 94 V	85 - 90 V
Corrente max • Максимальный ток	21 A	18 A
Fusibile di protezione ritardato • Плавкий пр-ль time lag	16 A	16 A
Fattore di potenza • Коэффициент мощности	0,85	0,85
Grado di protezione • Степень защиты	IP 23 S	IP 23 S
Classe d'isolamento • Класс изоляции	F	F
Temperatura ambiente • Рабочая температура	-10°C+40°C	-10°C+40°C
Dimensioni (mm) • Габариты (мм)	470x150x245	470x150x245
Peso (Kg) • Вес (кг)	10,00	10,00

FUNZIONI / ФУНКЦИИ	EXTERNAL	BUILT - IN
Campo di regolazione Plasma • Диап. при св-ке плазмой	12 – 35 A	12 – 25 A
Tipo innesco • Тип поджига дуги	PILOT ARC	PILOT ARC

PRESTAZIONI / ХАРАКТЕРИСТИКИ	EXTERNAL	BUILT - IN
Divisione (mm) • Отдел (мм)	12	10
Taglio qualità (mm) • Качество резки (мм)	10	6

Ferro • Железо
10 mm



Ferro • Железо
6 mm

