

Combination arrester V25, 4-pole 280 V




V 25-B+C/...: Combination arrester set, lightning and surge arrester Type 1+2 to DIN EN 61643-11 (B+C to VDE 0675 Part 6).

- With new Multibase base with multi connection terminals
- Complete unit consisting of cover and base, pre-mounted and ready for connection
- For TN systems
- Plug-in arrester with dynamic isolating device
- With visual function display
- Voltage protection level < 0,9 kV
- Encapsulated non-extinguishing zinc oxide varistor arrester for use in standard distributor housings
- Marked connections


Application example: Building with open-wire power supply or for setting up lightning protection equipotential bonding in residential buildings.

Dimensions



Type	Highest Version	Pack.	Weight	Item No.
	contin-	pcs	kg/100 pcs.	
	uous			
	voltage			
	V			
V25-B+C 4-280	280 4-pole	1	53,000	5094426

Connection options



V25-B+C 4-280

Nominal voltage V	U _N	230
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350) kA	I _{imp}	7
Total discharge current (10/350) kA	I _{total}	25
Nominal discharge current (8/20) kA	I _n	30
Arrester surge current (8/20) [total] kA	I _{total 8/20}	120
Maximum discharge current (8/20 μs) kA	I _{max}	50
		—
Voltage protection level kV	U _p	< 0,9
Response time ns	t _A	< 25
Maximum back-up fuse A		160
Temperature range °C	θ	-40+80
Division unit TE (17.5 mm)		4
Protection rating		IP20
Connection cross-section rigid mm ²		2,5-35
Connection cross-section, multi-wire mm ²		2,5-35
Connection cross-section, flexible mm ²		2,5-25